T3x Treadmill



- Matrix 4.2 Hp AC motor with Dynamic Response Drive System fine-tunes response based on footfall pattern for a smooth, consistent, natural workout
- Low 19 cm / 7.5" step-on height for easy accessibility
- Ultimate Deck System for superior performance and durability
- xID single-point user sign-in offers a seamless personal experience
- WiFi connectivity accommodates optional Matrix Asset Management system and Workout Tracking Network
- LED console display with expanded feedback offers intuitive operation

CONSOLE	
Dis play Type	Dot-matrix LED with profile display
Display Feedback	Time, Distance (Kilometers or Miles), Calories, Calories per Hour, Speed, Incline, Pace, Average Pace, Heart Rate, METs, Watts, Workout Profile
Secondary Data Display	No
User-defined Multi-language Display	Accessible only through manager menu: English, German, French, Italian, Spanish, Dutch, Portuguese, Japanese, Swedish, Finnish, Turkish, Polish
Workouts	Manual, Rolling Hills, Fat Burn, 5k, Target HR, Gerkin Protocol, Army PFT, Navy PR Marine PFT, Air Force PRT, Physical Efficiency Battery (PEB), WFI Protocol
CSAFE Ready-FitLinxx™ Certified	Yes
IPTV Compatible	No
Pro:Idiom Compatible	Optional - add-on TV
FitTouch™ Technology	No
One-button Start	Yes
On-the-fly Program Change	Yes
Integrated Vista Clear™ Television Technology	No
FITCONNEXION™ Ready	Yes
WiFi Enabled	Optional
Bluetooth Enabled	No
iPod® / iPhone® / iPad® Compatible	Charging only
Multimedia Playback	No
Personal Fan	No
Personal Trainer Portal Compatible	No
USB Port	Yes
Virtual Active™ Compatible	No
Asset Management Compatible	Yes
Workout Tracking Network Compatible	Yes
Web Connectivity	No
Facility Communication Portal/Calendar	No
RFID Compatible	No

Pause Function	Yes
Reading Rack	No
DRIVE SYSTEM	
Drive System	Matrix 4.2 hp AC Dynamic Response Drive System
FEATURES	
Deck Type	Ultimate hard-wax reversible 1" deck
Belt Type	Habasit, 2-ply commercial grade
Running Area	152 x 51 cm / 60" x 20"
Step-on Height	19 cm / 7.5"
Cushion System	Ultimate Deck™ cushioning system
Incline Range	0-15% (590-kg / 1,300-lb. thrust elevation motor)
Speed Range	0.8 - 20 km/h / 0.5 - 12 mph
Contact & Telemetric HR	Yes
Crossbar Controls	No
Tread Sense	No
NOTE	
Speed Rating	24.1 km/h / 15 mph rating good for users up to 159 kg / 350 lbs.
TECH CRECC	
TECH SPECS	
Power Requirements	20-amp dedicated circuit required, non-looped grounded
Electrical Receptacle & Plug	NEMA 5-20R 120v
Assembled Dimensions	215 x 85 x 142 cm / 84.6" x 33.5" x 56"
Max User Weight	182 kg / 400 lbs.
Assembled Weight	172 kg / 378 lbs.

186 kg / 409 lbs.

Shipping Weight